



MOTO PRO DOT 4 BRAKE FLUID

FULLY SYNTHETIC - BRAKE FLUID

PRODUCT DESCRIPTION:

Moto Pro Dot 4 Brake Fluid is made from high molecular weight polyalkylene glycol ethers and borate esters, to give a high boiling point fluid of DOT 4 quality. The formulation has been developed in a way that the vapour lock point can be sustained at a higher level than conventional glycol ether-based fluids during the service life of the product. It contains inhibitors to prevent the corrosion of metallic brake components and to reduce oxidation at increased temperatures.

APPLICATION:

Moto Pro Dot 4 Brake Fluid can be used for vehicles with anti-lock (ABS) braking systems, and hydraulic clutch systems requiring conventional fluids. Moto Pro Dot 4 Brake Fluid is recommended for passenger cars, commercial road transport, off-highway vehicles, agricultural tractors and motorcycles requiring DOT 4, SAE J1704 or ISO 4925 Class 4 fluid. Moto Pro Dot 4 Brake Fluid is miscible and compatible with high-quality DOT 3 and DOT 4 brake fluids. The optimal period of use for this brake fluid is, however, only ensured when it is used alone. It is recommended that the brake fluid be changed in accordance with the specifications from the vehicle manufacturer.

FEATURES & BENEFITS:

- Excellent elastomer compatibility.
- Assures a high degree of lubricating action on all moving components in the hydraulic brake circuit.
- Extremely high wet and dry boiling points.
- Excellent viscosity/temperature properties.
- Excellent braking response due to high boiling point of fluid.
- Highest thermal stability.

PERFORMANCE LEVEL: Meets and Exceeds:

- FMVSS 116 DOT 3 and DOT 4
- SAE J 1703 and J 1704
- ISO 4925 (Classes 3 & 4)
- JIS K 2233

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	BRAKE FLUID DOT 4
DRY ERBP	D-1120	°C	236
WET ERBP	D-1120	°C	160
Kinematic Viscosity @ 100C	D-445	-	2.10
Density @20°C	D-1298	g/cm ³	1.045
Kinematic Viscosity @ -40C	D-445	°C	1650
pH	D-1287	°C	8.2

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.