



## MOTO PRO UTV 10W-50

### FULLY SYNTHETIC ENGINE OIL

#### PRODUCT DESCRIPTION:

Moto Pro UTV 10W-50 is made specifically to operate in high heat conditions such as extreme ambient temperatures, slow speed high load or sustained high RPM conditions. Moto Pro UTV protects vital engine components, controls the harmful effects of oil oxidation and delivers maximum performance needed to protect the hardest working ORVs. The specially designed low traction, coefficient ester incorporated in this formula, reduces engine internal frictional losses and improves performance.

#### APPLICATION:

Moto Pro UTV 10W-50 is recommended for air cooled and water cooled, four-stroke engine' Off-Road Vehicles, Including: ATV and vehicles designed for extreme duty applications.

#### FEATURES & BENEFITS:

- Excellent wear protection.
- High shear stability and viscosity retention.
- Excellent wet clutch compatibility.
- High film strength for optimum lubrication.

#### PERFORMANCE LEVELS: Meets and Exceeds:

- API SN
- JASO MA2

#### TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	MOTO PRO UTV
<b>SAE Grades</b>			<b>10W-50</b>
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	121.1
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	17.45
Viscosity Index	D-2270	-	159
SP. Gravity @15°C/ 60°F	D-4052	g/cm3	0.865
Flash Point (min)	D-92	°C	230
Pour Point (max)	D-97	°C	-36
TBN	D-2896	Mg KOH/g	9
CCS, (°C)	D-5293	mPa.S	<7000 (-25)

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.