

GEAR OIL



Technical Data Sheet

MOTO PRO UTV DIFFERENTIAL GEAR OIL FULLY SYNTHETIC DIFFERENTIAL GEAR OIL

PRODUCT DESCRIPTION:

Moto Pro UTV Differential Gear Oil is a fully synthetic, high-quality differential lubricant specifically designed for UTV to maintain peak performance. The special additive system of Moto Pro UTV is formulated using the latest technology to protect vital transmission components, to last longer, control moisture and deliver maximum performance needed for high RPM, off-road vehicles. Moto Pro UTV fluid has excellent shear stability, ensuring that viscosity remains constant over the lifetime of the fluid. It provides superior chain and gear wear protection and reduces the effects of shock loading and will hold up extreme conditions.

APPLICATION:

Moto Pro UTV Differential Gear Oil is designed to be used in off-road vehicle differential, gearcase and transmission system.

FEATURES & BENEFITS:

- · Contains EP additives for extreme shock and wear protection over a range of temperature and speeds.
- Premium anti-wear formula provides total chain and gear wear protection.
- Reduces the effects of shock-loading.
- · Delivers smooth consistent operation.
- For use in four-stroke, off-road vehicle transmissions and gear cases.
- Prevents rust, oxidation, foam and corrosion of internal components.

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	VALUE
Kinematic Viscosity @100 °C	D445	cSt	7
Kinematic Viscosity @ 40 °C	D445	cSt	38.6
Viscosity Index	D2270	-	143
Pour Point	D97	°C	-42
SPECIFIC GRAVITY @ 15.6 °C	D4052	g /cm^3	0.852
Flash Point	D92	°C	228

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good tandards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.